D-Fi Hub 2

Sync an unlimited number of D-Fi-ready fixtures wirelessly and simultaneously with D-Fi Hub 2. A compact D-Fi wireless transmitter/receiver that sends and receives wireless DMX signals over an impressively long range while being fully FCC and R&TTE compliant. Compatible with the ILS Command, this unit is the perfect sidekick to your ILS rig. With a fastening strap, USB-C power out and more, ease of use and versatility are built right in to D-Fi Hub 2.

LO DESTACADO

- Compact, easy-to-use wireless D-Fi transmitter and receiver in a single unit
- Wirelessly synchronize an unlimited number of D-Fi-ready fixtures and receivers simultaneously
- Compatible with the ILS Command to wirelessly send or receive ILS protocols
- LED indicators clearly communicate the TX/RX status and wireless D-Fi frequencies
- USB-C passthrough powers additional devices
- Built-in hook and loop fastener strap and M10 threaded holes for direct mounting to truss
- Fully FCC/RTTE compliant

ESPECIFICACIONES

- DMX Channels : 3-pin XLR
- Operating Frequency : 2.412 to 2.484 GHz
- Input Voltage : 5 VDC, 2 A (external power supply: 100 to 240 VAC, 50/60 Hz)
- Weight : 0.2 lb (0.1 kg)
- Size : 3.9 x 3 x 1.6 in (100 x 77 x 41 mm)
- Approvals : CE, ROHS, FCC
- Max Unobstructed Distance : 656 ft (200 m)

LO QUE INCLUYE

- DFI-HUB 2
- Power cord
- Power supply
- Quick Reference Guide