

EZBeam Q3 ILS

LO DESTACADO

- Battery-operated wall accent and effect light all in one
- ILS compatibility for use in the ILS ecosystem
- D-Fi USB compatibility for wireless master/slave or DMX control
- Combine multiple units to create unique wall art effects
- 180° tilt range gives you lighting versatility
- No moving parts means silent operation, ideal for quiet environments
- Generate eye-catching effects with sound-activated and automated programs
- Convenient, wireless non-DMX control using the IRC-6 remote



ESPECIFICACIONES

- DMX Channels : 6, 9, 14 or 17
- DMX Connectors : 3-pin XLR
- Light Source : 3 LEDs (quad-color RGBA) 3.3 W, (1.3A), 50,000 hours life expectancy
- Strobe Rate : 0 to 31 Hz
- Beam Angle : 16°
- Coverage Angle : 24°
- Illuminance : 172 lux @ 2 m (per pod)
- Power Linking : 10 units @ 120 V; 18 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 55 W, 0.8 A @ 120 V, 60 Hz
- Weight : 7.6 lbs (3.4 kg)
- Size : 12 x 3.5 x 8.5 in (308 x 89 x 217 mm)
- Approvals : CE, UKCA, RoHS
- Optional Controllers : IRC-6, ILS Command
- Maximum Run Time (all on) : up to 9 hours
- Maximum Run Time (single color) : up to 20 hours
- Recharge Time : 5 hours

LO QUE INCLUYE

- EZBeam Q3 ILS
- Power cord
- Quick Reference Guide